



- 1 NOZZLE
(HIGH DENSITY POLYETHYLENE)
- 2 DISCHARGE VALVE
(MED. DENSITY POLYETHYLENE)
- 3 VALVE BODY
(POLYPROPYLENE)
- 4 PISTON
(MED. DENSITY POLYETHYLENE)
- 5 SPRING
(STAINLESS STEEL)
- 6 SHROUD - ERGO
(POLYPROPYLENE)
- 7 BALL VALVE
(GLASS, PLASTIC, STAINLESS STEEL)
- 8 TUBE RETAINER
(POLYPROPYLENE)
- 9 GASKET
(POLYETHYLENE FOAM)
- 10 CLOSURE 28-400
(POLYPROPYLENE)
- 11 DIP TUBE
(POLYPROPYLENE)
- 12 TRIGGER
(POLYPROPYLENE)

BECAUSE THE CLOSURE HAS A 1/2° DRAFT:

THE MAX *T* DIA OF 28.19[1.110] IS TAKEN AT THE BOTTOM OF THE CLOSURE

THE MIN *T* DIA OF 27.66[1.089] IS TAKEN AT 16.66[.656] FROM THE BOTTOM OF THE CLOSURE

THE MAX *E* DIA OF 25.81[1.016] IS TAKEN AT THE FIRST FULL THREAD

THE MIN *E* DIA OF 25.27[0.995] IS TAKEN AT 16.66[.656] FROM THE BOTTOM OF THE CLOSURE

"UNCONTROLLED"

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG10082

DESCRIPTION:

28-400 Trigger Sprayer