



70-450 CT CAP "FIS" FLAT TOP STACKING PANEL LID BUTTON WITH PLASISOL LINER MATERIAL . 75# T-4, 55# DK-9 PULL DOWN VACUUM B.O IN. HG. MAX. WITH A VACUUM RETURN 2.0 IN. HG. MIN.

NOTES

1) A RECESSED STACKING FEATURE INVOLVING A RAISED OUTSIDE EDGE IS ACHIEVED BY INCREASING THE HEIGHT OF FLAT TOP CAP BY APPROX. 0.030"

THE MAX. & MIN. INSIDE DIAMETER OF THE THREAD ARE DETERMINED BY ROUND MAX. & MIN. PLUG GAUGES. THE CLOSURE SHOULD PERMIT ENTRY OF THE MIN. GAUGE AND NO ENTRY, TO ENTRY WITH A SLIGHT DRAG ON THE MAX. GAUGE.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: