Dimensions	Measurements	
Outer Length	1200mm	47.25 inches
Outer width	1000mm	39.4 inches
Outer height	1346mm	53.1 inches
Capacity	Measurements	
Nominal	1249 liters	330 gallons
Brimful	1268 liters	335 gallons
Weight	Measurements	
tare weight	60Kg	132 lbs

	Construction		
Outer Container	Outer cage made of square tubular steel, welded, top closed with restraint bars, with four corner protectors, label plates total, two marking plate poly gray 26 X 23.5 (P)		
Inner Container	Blow molded, filling opening DN150 with external thread (CCS160x7), located in the middle of top section		
Filling opening	Screw Lid - FLAT RED SEAL		
Discharge valve	VLV 2 CYL QD VIT FS NAT - 81300038		

Materials		
Outer container:	Galvanized Steel, corrosion resistant	
Corner protector:	Post Consumer HDPE (black in color)	
Inner Container:	HDPE	
Screw lid:	HDPE (black in color)	
Gasket lid:	VITON	
2" plug:	2" NPT	
Pressure relief:	N/A	
Protection lid:	N/A	
screw lid:	HDPE	
Valve body:	CYL QD	
Gasket inner valve:	VITON	
Inner container to valve	PE	
Screw cap (valve):	PE	
Pallet:	Galvanized Steel, corrosion resistant, HDPE supports and valve tray	
Tamper evident shield valve:	PE	

Marking

UN CODE: 31HA1

Manufacturer MAUSER USA, LLC:

31HA1/Y/MM YR USA/MXXXX/3800Kg/2038Kg 1250L/57Kg/100kPa/MM YR MM YR

DISCLAIMER	DISTRIBUTED BY:	REF NO.:
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS, IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT	ipeline Packaging	g
THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.	DESCRIPTION:	