

	Material of Construction	Inner container Extrusion blow molding HDPE Inner container additives Natural Fluorination level Outer Container Galvanized tubular welded cage
Dimensions	Accessories	Corner protectors Black
Outer Length 1200mm 47.25" Outer width 1000mm 39.4" Outer height 1346mm 45.3"		Marking plates Valve side and back Large 26.5 X 15.75
Capacity		Fill Port cap 81610009 LID 6 BUNG VIT BLK FLAT RED C/S
Nominal 1250 liters 330 gallons Brimful 1277 Liters 336 gallons		Discharge Outlet 81300038 VLV 2 CYL QD VIT Inner container/valve Gasket Viton
Weight		Pallet Assembly COMPOSITE ASSY
tare weight 60KG 132 lbs		Inserts
add ons: <input type="checkbox"/> SPOUT METRIC <input type="checkbox"/> SECURITY LID <input type="checkbox"/> BAGGED <input type="checkbox"/> SPOUT NPT ASSY		Dip tubes
Required labels: <input checked="" type="checkbox"/> 1650 Kg Stack label <input checked="" type="checkbox"/> NCG Recollect label <input type="checkbox"/> NCG/Univar return label <input type="checkbox"/> EX-zones 1 and 2 safety Instructions		Marking SM 13 31HA1/Y/Mxxx/3800Kg/2038Kg/1250L/60KG/100Kpa/ MM Yr/MM YR
Notes		

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY: 	REF NO.: DWG30025
DESCRIPTION: 330 Gallon New IBC Tote	