





THREAD DETAIL INFORMATION 6 THREADS PER INCH, 0.167 PITCH 450° (1 1/4 TURNS FULL DEPTH THREAD)			
REFERENCE	TOLERANCE	DIMENSION	UNITS
Т	±0.010 [0.25]	1.638 [41.61]	in [mm]
E	±0.010 [0.25]	1.535 [38.99]	in [mm]
	±0.010 [0.25]	1.425 [36.20]	in [mm]
S'	±0.010 [0.25]	0.095 [2.41]	in [mm]
Н	±0.010 [0.25]	0.400 [10.16]	in [mm]
OAH	±0.010 [0.25]	1.072 [27.23]	in [mm]
BOTTOM OD	±0.010 [0.25]	1.460 [37.08]	in [mm]
PART WEIGHT	±0.50	4.50	g
MAXIMUM VOLUME	±5%	0.88 [26.0]	oz [cc]

**DISCLAIMER** 

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

REF NO.:

DESCRIPTION: