SPECIFICATIONS:

Diameter:	Range 22.75 - 23.25"	Target 23.00" (Mid-Panel)
Weight:	25.00 - 26 lbs.	25.5 lbs.
Height:	35.5 - 36"	35.75″
Sidewall Dist:	min 0.125"	0.150″
Bottom Dist:	min 0.125″	0.150″
Fill Capacity:	57.5 - 59.0 gal.	58.5 gal

- constructed with one-piece high-density, high-molecular weight, polyethylene, to provide strength and durability
- manufactured with virgin or post industrial resin
- bottom designed to maximize contact with the pallet for slip resistance
- designed with large labeling area on top
- designed with large diameter to add capacity and stability
- easily handled with standard drum-handling equipment
- designed to maximize usage of the road trailers when full or empty
- weatherproof
- easily reused or reconditioned for multiple trips
- available with (1) 2" NPT bung and (1) ¾" NPT bung or solid cover
- available in blue, black, or custom color

COVER SPECS:

RING SPECS:

Diameter: Gasket Thickness: 22.185" + 0.025" 0.490" + 0.025"

18 gauge steel Side lever lock with tab lock Diameter: 22.04" + 0.03"

	DISTRIBUTED BY:	REF NO.:
		DWG31006
DISCLAIMER	lipeline Packaging	
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.	DESCRIPTION: 57 Gallon Black HDPE OH Head with 2 in & .75 in Fittings, Lever Lock Ring	