



STEEL TIGHT HEAD DRUM (in accordance with DIN ISO 15750-2)			
Material:	ASTM A1008, CS Type B, Cold Rolled Sheet		
Description:	Longitudinal weld seam		
	Triple round seams at top and bottom		
	Two (2) W-Style Rolling Hoops		
	Suitable for container loading		
	Head designed for optimal drainability		
	Universal Seam Sealer #006HV		
External Paint:	Top:	Shell Red, PMS 485	
	Body:	Shell Red, PMS 485	
	Bottom:	Signal Red, RAL 3001	
Inner Drum Lining:		L-5X Olive Drab Phenolic	
UN Rating & Embossment:		UN1A1 / X1.8 / 300	
Inkjet:		Standard UN Mark, C-Panel	
Silk-Screen:		None	
BUNG CLOSURE SYSTEM (in accordance with DIN ISO 15750-3)			
Closures:	Type:	G3/4"	G2"
Flanges:	Type:	L-5X Olive Drab Phenolic Lined	L-5X Olive Drab Phenolic Lined
	Gasket:	EPDM	EPDM
Plugs:	Type:	L-5X Olive Drab Phenolic Lined	L-5X Olive Drab Phenolic Lined
	Gasket:	EPDM	EPDM
	Vented:	N/A	N/A
	Torque (lb-ft):	8 - 15	15 - 23
Cap Seals:	Type:	None	None
	Installed:	N/A	N/A
LOADING REQUIREMENTS			
Cardboard between layers. Air bags required to secure the load.			
*NOTES			

*Technical information subject to change, all dimensions approximate

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG30881

DESCRIPTION:

55 Gallon Red Steel Tight Head Drum, Lined