

TECHNICAL DATA

Fits Pails: PR1200, PR1300, PR1400, PR1700, PR1907, PR1910, PR2000, PR2300

Lid LR1940 - Tearstrip Lid with Gasket (EPDM Rubber)

Wall Thickness LR1940 2.16mm 0.085in

Weight (approx.) without bail LRT940 255g 8.99oz

Material HDPE

Thermal range -18°C (0°F) to 66°C (150°F)

Lid Colour Standard in White, other colors available.

TOP LOADING RESISTANCE

60kg (132lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production. Can be restricted by pail specifications.

OPENING & CLOSING

TO OPEN: Remove tear tab, then lift cover.

TO CLOSE: Place lid on pail, and use capping machine, or press on with hands/mallet.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

Lid: LR1940



DIMENSIONS	CM	INCHES
Lid Height	3.505	1.38
External Diameter	31.72	12.49

PACKAGING OF LIDS

- Warehousing of 1940 Lids:
 - 300 per tray - 600 per pallet
 - Max 4 pallets high for warehousing of lids

DISTRIBUTED BY:



REF NO.:

DWG30521

DESCRIPTION:

3.5-6 Gallon HDPE Plastic Pail Cover, Tear Tab, EPDM Gasket

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.