



DISTRIBUTED BY:



REF NO.:

DWG31151

DESCRIPTION:

75 Liter CurTec Nestable Drum HDPE Plastic
Open Head Drum w/ Blue Screw Top Cover

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

Capacity	Liters	US Gallons
Brimful	80	21.13
When closed	76	20.08

Hazardous material information	
Hazardous material type	Solids
Packaging group	I – II – III
UN marking	UN/1H2/X75/S/--/B/CURTEC-140180
Maximum gross mass (kg)	X=75 Y=113 Z=150

Weight	Grams	Ounces
Drum	3025	106.70
Handles	90	3.18
Lid	716	25.26
Gasket	44	1.55
Total	3875	136.69

Weight tolerance
All products have a tolerance of $\pm 4\%$ of the initial weight mentioned on this data sheet

Dimensional tolerances	%
Height	± 2.5
Diameter	± 1.5

Wall thickness	mm
Minimal wall thickness	≥ 2.2
Nominal wall thickness	≥ 2.7

Other information
 Maximum filling temperature is 70°C/ 158°F
 Contents must have cooled to 30°C/ 86°F before containers can be closed and stacked
 DoC available on request
 UN certificate available on request
 MVTR declaration available on request
 Watertightness declaration available on request
 User manual available on request
 Preparation for future valve option integrated in drum
 All drums can be made tamper evident with application of compact seal # 7800

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG31151

DESCRIPTION:

75 Liter CurTec Nestable Drum HDPE Plastic
Open Head Drum w/ Blue Screw Top Cover